

MATERIAL SAFETY DATASHEET

I. PRODUCT IDENTIFICATION

PRODUCTS NAME(s) : Prime Gel API, Prime Gel Natural, Western Extra High Yield **PRODUCT CODE:** AB3A005
GENERIC NAME: Bentonite **MSDS CODE NO.** A202PAB3A005

CHEMICAL NAME: Sodium /Calcium Aluminum Silicate **CASE REGISTRY NO.** 1302-78-9*
MANUFACTURING : WESTERN CLAY CO. **TELEPHONE NUMBERS:**
ADDRESS: 508 East Center **EMERGENCY:** 213-664-2121
Aurora, Utah 84620 **CHEMTREC:** 800-424-9300
BUSINESS: 800-982-7960

II. HAZARD IDENTIFICATION

HEALTH/PHYSICAL HAZARDS: Material dusts containing less than 1% free crystalline silica (quartz) Are classified as nuisance particulates. Exposure to these dusts may cause irritation to eyes, ears, throat, and upper respiratory tract. This materials dust may contain more than 1% free silica as Quartz. Chronic (long term) exposure to air born free silica at levels higher than TLV=s may lead to the development of silicosis or other respiratory problems. (See Section VI)

HAZARD LISTING: Nuisance Particles are listed by ACGIH. Free Crystalline Silica as Quartz is listed by OSHA and ACGIH as a Hazardous Material.

III. PHYSICAL DATA

Melting Point: (1450 Deg C)

Bulking Value 90 lbs

Solubility in Water : Insoluble, Forms Colloidal Suspension pH : 8-10

Appearance : Tan, Light Green powder

Density : 70lb / cu. Ft Powder or Compact Granular

IV. FIRE AND EXPLOSION DATA

Flash Point : N.A.

Flammable Limits : LEL: NA UEL: NA

Special Fire Fighting Procedures : NA

Unusual Fire and Explosion Hazards : None, Product Will Not Support Combustion.

Extinguishing Media : None For Product, Any Media can Be Used For Packaging

V. REACTIVITY

Stability : Stable

Hazardous Polymerization : None

Incompatibility : None

Hazardous Decomposition Products : None

NA = Not Applicable

ND = Not Determined

Date Prepared : August 27, 2007

VI. HEALTH HAZARD INFORMATION

ROUTES OF EXPOSURE AND EFFECTS

Skin : Possible drying resulting in dermatitis.

Eyes : Mechanical Irritant.

Inhalation : (Acute, Short Term) Exposure to excessive concentrations of dust may cause irritation of the Nose, Throat, And Upper Respiratory Tract. (Chronic, Long Term) Chronic exposure to crystalline silica such as quartz were levels exceed TLV=s can cause Silicosis and other respiratory problems. Short term exposure to very high concentrations may lead to increased risk and accelerated onset of silicosis and respiratory damage. Silicosis is a progressive, degenerative, disabling, and sometimes fatal lung disease characterized by coughing, shortness of breath, wheezing, and fibrotic changes in the lungs with scarring and nodular formation.

Ingestion : Accidentally this material will generally cause no adverse effects. Minor intestinal irritation is possible.

Permissible Exposure Limits :
(For air contaminants)

	OSHA PEL (8hr. TWA)	ACGIH TLV
Bentonite as nuisance dust		
Total dust	15mg/cubic meter	ND
Respirable dust	5mg/cubic meter	ND
Crystalline Quartz (respirable)	0.1mg/cubic meter	0.1mg/cubic meter

Where crystalobalite or tridymite are present use 2 of the PEL or TLV value for crystalline quartz.

Carcinogenicity : Bentonite is not listed by NTP, IARC or OSHA. IARC, 1987, concludes that there is limited evidence suggesting the carcinogenicity in humans of inhaled crystalline silica (IARC Class 2A).

Acute Oral LD : ND

Acute Dermal LD :

Aquatic Toxicology LC : ND

Emergency and First Aid Procedures

Skin : Wash with soap and water until clean

Eyes : Flush with water until irritation ceases. Do not rub eyes.

Inhalation : Move to area free from dust. If symptoms of irritation persist contact physician. Inhalants may aggravate existing respiratory illness.

VII. HANDLING AND USE PRECAUTIONS

Steps to be taken if material is released or spilled : Avoid breathing dust; wear respirator approved for silica bearing dust. Vacuum up to avoid generating airborne dust. Avoid using water. Product is slippery when wet.

Waste Disposal Methods : Product should be disposed of in accordance with applicable local, state, and federal regulations.

Handling and Storage Precautions : Use NIOSH/MSHA respirators approved for silica bearing dust when free silica containing airborne bentonite dust levels exceed PEL/TLV=s. Clean up spills promptly to avoid making dust. Storage area floors may become slippery when wet.

VIII. INDUSTRIAL HYGIENE CONTROL MEASURES

Ventilation Requirements : Mechanical, general room ventilation. Use local ventilation to maintain PEL=s/TLV=s.

Respirator : Use respirator approved by NIOSH/MSHA for silica bearing dust.

Eye Protection : Use safety glasses or goggles to minimize material from getting into eyes.

Gloves : Generally not necessary.

Other Protective Clothing or Equipment : None

IX. SPECIAL PRECAUTIONS

Avoid prolonged inhalation of airborne dust.

DEPARTMENT OF TRANSPORTATION INFORMATION

Shipping Name : Common Ground Clay (NOIBN) Hazard Class : Not Hazardous Cautionary Labeling : None required

This information is taken from sources or based upon data believed to be reliable, however, Western Clay Co. makes no warranty as to the absolute correctness or sufficiency of any of the foregoing or that additional or other special protective measures may not be required under unusual or particular conditions which may be associated with normal use of this product. Since the use or misuse of this product is not within the control of Western Clay Co. it is the users obligation to assure conditions of safe use and disposal of this product. Seller warrants that this product conforms to the specifications stated herein. Buyer assumes all risks associated with the possession, use, mixing, blending, treatment, storage, disposal, transportation, and handling of the product, whether alone or in combination with other substances. SELLER MAKES NO OTHER WARRANTY OF ANY KIND WHATEVER, EXPRESS OR IMPLIED, AND ALL OTHER WARRANTIES, INCLUDING WARRANTIES OF QUALITY, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE DISCLAIMED. Seller's liability is limited to the product price.