



# PONDSEAL-4

Natural Unaltered High Swelling Sodium Bentonite

## Description

**PONDSEAL-4** is an all natural unaltered high swelling sodium bentonite. **PONDSEAL-4's** high swelling properties makes it a preferred choice for all your compacted or pure layer water containment membranes.

## Application

- Soil Sealant
- Reservoirs
- Municipal Landfills
- Sanitation Lagoons
- Hazardous Storage
- Tailings Ponds
- Leach Pads
- Canals
- Tank Farms
- Ponds

## Typical Properties

### Product Specification

### Typical PONDSEAL-4

Color	Tan
Density	70 lbs/ft <sup>3</sup> (compact)
pH	8.5 to 9.0
Swell	20 cc / 1000%
Moisture	8 to 13 wt. %

## Sieve Analysis

SCREEN MESH	PERCENT	SCREEN MESH	PERCENT
+4	1%	+80	80%
+6	14%	+100	90%
+10	40%	+200	95%
+20	58%	-200	5%
+30	66%		

## Advantages

- 100% Natural
- Ultra Low Permeability Barrier
- Wide range of use
- Great Containment Barrier
- Mixes quickly and easily
- Excellent hard water performance

## Mixing

The percent of **PONDSEAL-4** used should be determined thru permeability testing and user specification requirements.

Permeability testing is available at Redmond Minerals upon request.

## Packaging

**PONDSEAL-4** is available in 50 lb plastic bags - 49 bags per/pallet, 3,000 lb super sacks, and bulk shipments.

:



Distributed by:

H & H Environmental, Inc. PO Box 4581 Grand Jct., CO 81502 (800) 952-0802 www.hhenv.com

To the best of our knowledge and belief, the above information is accurate. Because the conditions of handling and use are beyond our control, we cannot guarantee results, and assume no liability for damages incurred in using our product. 7/15